



**1 KERN KBP-V20 IP65**

**Platform**

**Features**

- Stainless steel-weighing plate, **A** painted steel base
- 1 load cell, aluminium, silicone-coated, IP65, OIML-R60-approved, class III, 3000 e
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard
- Preparation for easy assembly of the ESD earthing kit on the weighing bridge



STANDARD

IP 65 1 DAY 2 DAYS

KPB 600



**2 KERN KFP-V20 IP65**

**Platform**

**Features**

- Stainless steel-weighing plate, **B** painted steel base
- 1 load cell, aluminium, silicone-coated, IP65, OIML-R60-approved, class III, 3000 e
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard



STANDARD

IP 65 1 DAY 2 DAYS

KPB 600



**3 KERN KXP-V20 IP65**

**Platform**

**Features**

- Stainless steel-weighing plate, **C** painted steel base, extremely rigid, wing design
- 1 load cell, aluminium, silicone-coated, IP65, OIML-R60-approved, class III, 3000 e
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard



STANDARD

IP 65 1 DAY

KPB 600



Model	Weighing capacity	Readability	Verification value	Minimal load	Cable length	Net weight	Weighing plate
	[Max] kg	[d] g	[e] g	[Min] g	approx. m	approx. kg	W×D×H mm
<b>1 Platform KBP-V20 IP65</b>							
KBP 6V20LM	3   6	0,2	1   2	20   40	2,5	3,8	300×300×110
KBP 15V20M	6   15	0,5	2   5	40   100	2,5	3,8	300×240×110
KBP 15V20LM	6   15	0,5	2   5	40   100	2,5	7	400×300×110
KBP 30V20M	15   30	1	5   10	100   200	2,5	7	400×300×110
KBP 60V20M	30   60	2	10   20	200   400	2,5	7	400×300×110
KBP 60V20LM	30   60	2	10   20	200   400	2,5	10	500×400×120
KBP 150V20M	60   150	5	20   50	400   1000	2,5	10	500×400×120
KBP 150V20LM	60   150	5	20   50	400   1000	2,5	19	650×500×150
KBP 300V20M	150   300	10	50   100	1000   2000	2,5	19	650×500×150
KBP 600V20M	300   600	20	100   200	2000   4000	2,5	42	800×600×200
<b>2 Platform KFP-V20 IP65</b>							
KFP 3V20M	3	0,1	1	20	2,5	3,4	230×230×103
KFP 6V20M	6	0,2	1   2	20   40	2,5	4,4	230×230×103
KFP 6V20LM	6	0,2	1   2	20   40	2,5	3,8	300×240×105
KFP 15V20M	6   15	0,5	2   5	40   100	2,5	3,8	300×240×105
KFP 15V20LM	6   15	0,5	2   5	40   100	2,5	7	400×300×114
KFP 30V20SM	15   30	1	5   10	100   200	2,5	3,8	300×240×105
KFP 30V20M	15   30	1	5   10	20	2,5	7	400×300×114
KFP 30V20LM	15   30	1	5   10	20	2,5	10	500×400×124
KFP 60V20M	30   60	2	10   20	200   400	2,5	7	400×300×114
KFP 60V20LM	30   60	2	10   20	200   400	2,5	10	500×400×124
KFP 150V20M	60   150	5	20   50	400   1000	2,5	10	500×400×124
KFP 150V20LM	60   150	5	20   50	400   1000	2,5	19	650×500×136
KFP 300V20M	150   300	10	50   100	1000   2000	2,5	19	650×500×136
KFP 600V20AM	600	20	200	4000	2,5	42	800×600×189
<b>3 Platform KXP-V20 IP65</b>							
KXP 6V20LM*	3   6	0,2	1   2	20   40	3	3,8	300×240×90
KXP 15V20M*	6   15	0,5	2   5	40   100	3	6	300×240×90
KXP 15V20LM*	6   15	0,5	2   5	40   100	3	8	400×300×90
KXP 30V20M*	15   30	1	5   10	100   200	3	8	400×300×90
KXP 30V20LM*	15   30	1	5   10	100   200	3	22	500×400×125
KXP 60V20M*	30   60	2	10   20	200   400	3	11	400×300×90
KXP 60V20LM*	30   60	2	10   20	200   400	3	17	500×400×125
KXP 150V20M*	60   150	5	20   50	400   1000	3	18	500×400×125
KXP 150V20LM*	60   150	5	20   50	400   1000	3	34	650×500×135
KXP 300V20M*	150   300	10	50   100	1000   2000	3	34	650×500×135

\* ONLY WHILE STOCKS LAST!

