



Mounted phase contrast condenser



Simple PH condenser with 40× PH slide

Lab Line

High-quality phase contrast microscope – specially pre-configured with a series of options for flexible expansion

Features

- We have developed this series specially for general applications with phase contrast method. In addition, the stable, modular construction system of the OBL series offers many more options
- Depending on the application, there is a choice of models with strong, infinitely dimmable 3W LED or 20W halogen illumination (Philips)
- A special fixed, pre-centred phase contrast condenser as well as field diaphragm give you a simplified Koehler illumination and thereby a powerful phase-contrast display of your sample
- The large mechanical stage and its specimen holder holds up to two samples at the same time and is quick and easy to focus using a coaxial coarse and fine focusing knob on both sides

- A large selection of eyepieces, objectives and colour filters, a simple polarising unit as well as further phase contrast units are available to you as accessories
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of delivery
- A C-mount adapter is required to connect a camera to the trinocular version. You can select this adapter from the following model outfit list
- Please find detailed information in the following model outfit list

Scope of application

 Haematology, urology, gynaecology, dermatology, pathology, microbiology and parasitology, immunology, Sewage treatment plants, oncology, entomology, vets, water analysis and breweries

Applications/Samples

 Specially for extremely translucent, thin, low-contrast, challenging samples
 (e.g. living mammal cells, bacteria, tissue)
 with phase contrast

Technical data

- Infinity optical system
- Quadplex nosepiece
- Siedentopf 30° inclined/360° rotatable
- Diopter adjustment: One-sided
- Overall dimensions W×D×H 395×200×380 mm
- Net weight approx. 6,7 kg

STANDARD OPTION OPTI

Model	Standard configuration

KERN	Tube	Eyepiece	Objective quality	Objectives	Illumination
OBL 146	Binocular	HWF 10×/Ø 20 mm	Infinity E-Plan/ Plan	4×/PH10×/	3 W LED (transmitted)
OBL 156	Trinocular	HWF 10×/Ø 20 mm	Infinity E-Plan/ Plan	PH40×/100×	3 W LED (transmitted)



Λ

Nodel outfit		Model KERN		Order number
		OBL 146	OBL 156	_
	HWF 10×/ø 20 mm	44	44	OBB-A1404
yepieces 23,2 mm)	WF 16×/Ø 13 mm	00	00	OBB-A1354
,	HWF 10×/ø 20 mm (with Pointer)	0	0	OBB-A1448
	4×/0,11 W.D. 12,1 mm	✓	✓	OBB-A1161
	10×/0,25 W.D. 2,1 mm	0	0	OBB-A1159
	40×/0,65 (spring-loaded) W.D. 0,58 mm	0	0	OBB-A1160
finity Plan objectives	100×/1,25 (oil) (spring-loaded) W.D. 0,19 mm	✓	✓	OBB-A1158
02,0011100	Plan 20×/0,40 (spring-loaded) W.D. 2,41 mm	0	0	OBB-A1250
	Plan 60×/0,80 (spring-loaded) W.D. 0,33 mm	0	0	OBB-A1270
	Plan 100×/1,15 (water) (spring-loaded) W.D. 0,18 mm	0	0	OBB-A1437
inocular tube	 Butterfly 30° inclined/360° rotatable Interpupillary distance 50 – 75 mm (for infinity system) Diopter adjustment: One-sided 	✓	0	OBB-A1578
rinocular tube	 Butterfly 30° inclined/360° rotatable Interpupillary distance 50 - 75 mm Light distribution 20:80 (for infinity system) Diopter adjustment: One-sided 	0	✓	OBB-A1582
lechanical stage	 Stage size W×D 145×130 mm Travel 76×52 mm Coaxial coarse and fine focusing knobs, scale: 2 μm Two slide holder 	~	✓	
H condenser	Abbe N.A. 1,25 precentered, for bright field and phase contrast	✓	✓	OBB-A1398
	Infinity PH-Plan objective 10×	✓	✓	OBB-A1390
	Infinity PH-Plan objective 20×	0	0	OBB-A1391
	Infinity PH-Plan objective 40×	✓	✓	OBB-A1392
	Infinity PH-Plan objective 100×	0	0	OBB-A1393
hase contrast units	PH slide 10×	✓	✓	OBB-A1399
	PH slide 20×	0	0	OBB-A1400
	PH slide 40×	✓	✓	OBB-A1401
	PH slide 100×	0	0	OBB-A1402
	Centering eyepiece	✓	✓	
arkfield ondenser	N.A. 0,85 – 0,91 (dry, paraboloid)	0	0	OBB-A1422
lumination	3 W LED illumination system (transmitted) (non-rechargeable)	✓	✓	
	Blue (built-in)	✓	✓	
olour filters	Green	✓	✓	OBB-A1188
r transmitted umination	Yellow	0	0	OBB-A1165
	Grey	0	0	OBB-A1183
	0,5× (focus adjustable)		0	OBB-A1515
C-Mount	1×		0	OBB-A1514

✓ = Included with delivery

O = Option

