

### Compound Microscope KERN OBS-1

#### Note

Please request special conditions for a classroom set



OBS 101



OBS 104



OBS 106



Objectives OBS



### Educational Line

## The school microscope – For the first steps in microscopy and for use in biology lessons

#### Features

- The KERN OBS range is a solid and simple school microscope range, which is easy to use due to its intuitive control elements
- The continuously dimmable 0.5W LED guarantees optimum illumination of the samples and also ensures long service life. Mobile use is also no problem through the use of rechargeable batteries
- The simple 0.65 condenser on the OBS 101 (condenser disc) and the OBS 102 (fixed condenser) ensures the very best concentration of light and illumination of the sample. The OBS 103, 104, 105 and 106 models have a 1.25 Abbe condenser which is height-adjustable and can therefore be

- focussed and has an aperture diaphragm, which ensures the very best concentration of light
- To focus the object, all models have a coarse and fine focusing knob on both sides. The mechanical stage enables you to work with the samples and move them rapidly (only for OBS 105, 106)
- A large selection of different eyepieces and objectives is also available
- Please find detailed information in the following model outfit list

#### Scope of application

- Primary school, secondary school, training, hobby use


#### Applications/Samples

- Translucent, thin, high-contrast, less complex samples (e.g. plant tissue, coloured cells/parasites)

#### Technical data

- Finite optical system (DIN)
- Triple (OBS 101, 102) or quadplex (OBS 103, 104, 105, 106) nosepiece
- Tube 45° (OBS 101, 102, 103, 105) or 30° (OBS 104, 106) inclined/360° rotatable
- Diopter adjustment: Both-sided (for binocular models)
- Overall dimensions W×D×H 130×300×310 mm
- Net weight approx. 3 kg

STANDARD



not OBS 101, 102

#### Model

Standard configuration

KERN	Tube	Eyepiece	Objective quality	Objectives	Illumination	Stage
OBS 101	Monocular	WF 10×/∅ 18 mm	Achromatic	4×/10×/40×	0,5W LED (transmitted) (battery incl., rechargeable)	fix
OBS 102	Monocular	WF 10×/∅ 18 mm	Achromatic		0,5W LED (transmitted) (battery incl., rechargeable)	fix
OBS 103	Monocular	WF 10×/∅ 18 mm	Achromatic		0,5W LED (transmitted) (battery incl., rechargeable)	fix
OBS 104	Binocular	WF 10×/∅ 18 mm	Achromatic		0,5W LED (transmitted) (battery incl., rechargeable)	fix
OBS 105	Monocular	WF 10×/∅ 18 mm	Achromatic		0,5W LED (transmitted) (battery incl., rechargeable)	mechanical
OBS 106	Binocular	WF 10×/∅ 18 mm	Achromatic		0,5W LED (transmitted) (battery incl., rechargeable)	mechanical

Model outfit	Model KERN						Order number	
	OBS 101	OBS 102	OBS 103	OBS 104	OBS 105	OBS 106		
<b>Eyepieces</b> (23,2 mm)	WF 10×/∅ 18 mm	✓	✓	✓	✓✓	✓	✓✓	OBB-A1473
	WF 16×/∅ 13 mm	○	○	○	○○	○	○○	OBB-A1474
	WF 20×/∅ 11 mm	○	○	○	○○	○	○○	OBB-A1475
	WF 10×/∅ 18 mm (with Pointer)	○	○	○	○	○	○	OBB-A1561
<b>Achromatic objectives</b>	4×/0,10 W.D. 18,0 mm	✓	✓	✓	✓	✓	✓	OBB-A1476
	10×/0,25 W.D. 7,0 mm	✓	✓	✓	✓	✓	✓	OBB-A1477
	40×/0,65 (spring-loaded) W.D. 0,53 mm	✓	✓	✓	✓	✓	✓	OBB-A1478
	60×/0,85 (spring-loaded) W.D. 0,1 mm	○	○	○	○	○	○	OBB-A1479
	100×/1,25 (oil) (spring-loaded) W.D. 0,07 mm	○	○	○	○	○	○	OBB-A1480
<b>E-Plan objectives</b>	4×/0,10 W.D. 14,5 mm	○	○	○	○	○	○	OBB-A1562
	10×/0,25 W.D. 5,65 mm	○	○	○	○	○	○	OBB-A1563
	40×/0,65 (spring-loaded) W.D. 0,85 mm	○	○	○	○	○	○	OBB-A1564
	100×/1,25 (oil) (spring-loaded) W.D. 0,07 mm	○	○	○	○	○	○	OBB-A1565
	100×/0,80 (dry) (spring-loaded) W.D. 0,15 mm	○	○	○	○	○	○	OBB-A1442
Plan 100×/1,0 (water) (spring-loaded) W.D. 0,18 mm	○	○	○	○	○	○	OBB-A1441	
<b>Monocular tube</b>	45° inclined/360° rotatable	✓	✓	✓		✓		OBB-A1471
<b>Binocular tube</b>	<ul style="list-style-type: none"> <li>• 45° inclined/360° rotatable</li> <li>• Interpupillary distance 55-75 mm</li> <li>• Diopter adjustment: Both-sided</li> </ul>				✓		✓	OBB-A1472
<b>Fixed stage</b>	<ul style="list-style-type: none"> <li>• Stage size W×D 110×120 mm</li> <li>• Coaxial coarse and fine focusing knobs, scale: 2,5 µm</li> </ul>	✓	✓	✓	✓			
<b>Mechanical stage</b>	<ul style="list-style-type: none"> <li>• Stage size W×D 115×125 mm</li> <li>• Travel 75×18 mm</li> <li>• Coaxial coarse and fine focusing knobs, scale: 2,5 µm</li> </ul>					✓	✓	
<b>Condenser</b>	Simple condenser N.A. 0,65	✓						
	Simple condenser N.A. 0,65 (aperture diaphragm)		✓					
	Abbe N.A. 1,25 (aperture diaphragm)			✓	✓	✓	✓	
<b>Illumination</b>	0,5 W LED illumination system (transmitted) (rechargeable)	✓	✓	✓	✓	✓	✓	
<b>Colour filters for transmitted illumination</b>	Blue			✓	✓	✓	✓	OBB-A1466
	Green			○	○	○	○	OBB-A1467
	Yellow			○	○	○	○	OBB-A1468
	Grey			○	○	○	○	OBB-A1184

✓ = Included with delivery

○ = Option

<b>360° rotatable microscope head</b>	<b>Fluorescence illumination for compound microscopes</b> With 100 W mercury lamp and filter	<b>Integrated scale</b> In the eyepiece	<b>Battery operation</b> Ready for battery operation. The battery type is specified for each device.
<b>Monocular Microscope</b> For the inspection with one eye	<b>Fluorescence illumination for compound microscopes</b> With 3 W LED illumination and filter	<b>SD card</b> For data storage	<b>Battery operation rechargeable</b> Prepared for a rechargeable battery operation
<b>Binocular Microscope</b> For the inspection with both eyes	<b>Phase contrast unit</b> For a higher contrast	<b>USB 2.0 interface</b> For data transmission	<b>Plug-in power supply</b> 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
<b>Trinocular Microscope</b> For the inspection with both eyes and the additional option for the connection of a camera	<b>Darkfield condenser/unit</b> For a higher contrast due to indirect illumination	<b>USB 3.0 interface</b> For data transmission	<b>Integrated power supply unit</b> Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
<b>Abbe Condenser</b> With high numerical aperture for the concentration and the focusing of light	<b>Polarising unit</b> To polarise the light	<b>WIFI data interface:</b> For transmitting of the picture to a mobile display device	<b>Package shipment</b> The time required to manufacture the product internally is shown in days in the pictogram.
<b>Halogen illumination</b> For pictures bright and rich in contrast	<b>Infinity system</b> Infinity corrected optical system	<b>HDMI digital camera</b> For direct transmitting of the picture to a display device	<b>Pallet shipment</b> The time required to manufacture the product internally is shown in days in the pictogram.
<b>LED illumination</b> Cold, energy-saving and especially long-life illumination	<b>Zoom magnification</b> For stereomicroscopes	<b>PC software</b> To transfer the measurements from the device to a PC.	
<b>Incident illumination</b> For non-transparent objects	<b>Auto-focus</b> For automatic control of the focus level	<b>Automatic temperature compensation</b> For measurements between 10 °C and 30 °C	
<b>Transmitting illumination</b> For transparent objects	<b>Parallel optical system</b> For stereomicroscopes, enables fatigue-proof working	<b>Protection against dust and water splashes IPxx:</b> The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013	
<b>Fluorescence illumination</b> For stereomicroscopes			

## Abbreviations

<b>C-Mount</b>	Adapter for the connection of a camera to a trinocular microscope	<b>SLR camera</b>	Single-Lens Reflex camera
<b>FPS</b>	Frames per second	<b>SWF</b>	Super Wide Field (Field number at least $\varnothing$ 23 mm for 10 $\times$ eyepiece)
<b>H(S)WF</b>	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	<b>W.D.</b>	Working Distance
<b>LWD</b>	Long Working Distance	<b>WF</b>	Wide Field (Field number up to $\varnothing$ 22 mm for 10 $\times$ eyepiece)
<b>N.A.</b>	Numerical Aperture		