

Load Cells SAUTER CR Q1 · CR P1 · CR Y1



Fig. shows accessories, load corner **1** SAUTER CE Q42901, for further accessories please visit our online shop



CR Q1 Load cells made of stainless steel

Technical data

- Accuracy in accordance with OIML R60 C1
- RoHS compliant
- Dust and spray protection to IP68 (in accordance with EN 60529), hermetically encapsulated
- Stainless steel
- Area of application: Weight measurement as well as compressive force
- Suitable for vehicle scales, funnel scales, vehicle testing equipment, test stands
- Nominal sensitivity: 2 mV/V
- Cable length approx. 10 m

Accessories CR Q1:

- **1** Load corner, steel, galvanised, suitable for CR Q1 with nominal load ≤ 10 t, SAUTER CE Q42901
- Load corner, steel, galvanised, suitable for CR Q1 with nominal load ≥ 20 t, SAUTER CE Q42902
- Load corner, steel, rustproof, suitable for CR Q1 with nominal load ≤ 10 t, SAUTER CE RQ42901
- Load corner, steel, rustproof, suitable for CR Q1 with nominal load ≥ 20 t, SAUTER CE RQ42902



Model Nominal load

SAUTER

CR 2500-1Q1	2,5 t/25 kN
CR 5000-1Q1	5 t/50 kN
CR 10000-1Q1	10 t/100 kN
CR 20000-1Q1	20 t/200 kN
CR 30000-1Q1	30 t/300 kN

** up to max. 25 t/250 kN


CR P1 Load cells made of stainless steel

Technical data

- Accuracy in accordance with OIML R60 C3
- RoHS compliant
- Dust and spray protection to IP68 (in accordance with EN 60529), hermetically encapsulated
- Stainless steel
- Area of application: Weight measurement as well as compressive force
- Suitable for truck scales, suspended scales, silo scales and other diverse scales, test stands, etc.
- Nominal sensitivity: 1–2 mV/V, depending on nominal load
- Cable length up to 1000 kg: 3 m
Cable length from 2000 kg: 6 m

Accessories CR P1:

- Load corner for CR 1000-3P1, CR 250-3P1, CR 500-3P1 Steel, incl. pressure piece, SAUTER CE P244011
- Pressure piece for CR 1000-3P1, CR 250-3P1, CR 500-3P1 steel, SAUTER CE P244012
- Load corner for CR 2000-3P1 steel, rustproof, incl. pressure piece, SAUTER CE P244021
- Pressure piece for CR 2000-3P1 steel, rustproof SAUTER CE P244022



Model Nominal load

SAUTER

CR 60-3P1	60 kg/0,6 kN
CR 130-3P1	130 kg/1,3 kN
CR 250-3P1	250 kg/2,5 kN
CR 500-3P1	500 kg/5 kN
CR 1000-3P1	1000 kg/10 kN
CR 2000-3P1	2000 kg/20 kN

* up to max. 500 kg/5 kN


CR Y1 Load cells made of alloyed steel

Technical data

- High precision (comprehensive Error 0,05 % F.S.)
- Accuracy in accordance with OIML R60 C1
- RoHS compliant
- Dust and spray protection to IP68 (in accordance with EN 60529), hermetically encapsulated
- Stainless steel
- Area of application: for weight, tensile and compressive force measurement
- Suitable for weight measurement as well as force and force test stands
- Force transmission via pressure piece or threaded hole
- Nominal sensitivity: 2 mV/V
- Pressure piece included in delivery
- Thread for pressure piece or other force application: up to 5000 kg M16×1,5, from 10000 kg M32×1,5
- Cable length approx. 3 m

Tip

- Further details and technical data sheet as well as an extensive range of accessories can be found at



Model Nominal load

SAUTER

CR 500-1Y1	0,5 t/5 kN
CR 1000-1Y1	1 t/10 kN
CR 5000-1Y1	5 t/50 kN
CR 10000-1Y1	10 t/100 kN
CR 20000-1Y1	20 t/200 kN

* up to max. 500 kg/5 kN

<p>Adjusting program (CAL) For quick setting of the instrument's accuracy. External adjusting weight required</p>	<p>Bluetooth* data interface To transfer data from the balance/measuring instrument to a printer, PC or other peripherals</p>	<p>Measuring units Weighing units can be switched to e.g. non-metric. Please refer to website for more details</p>	<p>Conformity assessment Models with type approval for construction of verifiable systems</p>
<p>Calibration block Standard for adjusting or correcting the measuring device</p>	<p>WIFI data interface To transfer data from the balance/measuring instrument to a printer, PC or other peripherals</p>	<p>Measuring with tolerance range (limit-setting function) Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model</p>	<p>DAkkS calibration possible The time required for DAkkS calibration is shown in days in the pictogram</p>
<p>Peak hold function Capturing a peak value within a measuring process</p>	<p>Data interface infrared To transfer data from the measuring instrument to a printer, PC or other peripheral devices</p>	<p>Protection against dust and water splashes IPxx The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989 +A1:1999+A2:2013</p>	<p>Factory calibration (ISO) The time required for factory calibration is specified in the pictogram</p>
<p>Scan mode Continuous capture and display of measurements</p>	<p>Control outputs (optocoupler, digital I/O) To connect relays, signal lamps, valves, etc.</p>	<p>Battery operation Ready for battery operation. The battery type is specified for each device</p>	<p>Package shipment The time required for internal shipping preparations is shown in days in the pictogram</p>
<p>Push and Pull The measuring device can capture tension and compression forces</p>	<p>Analogue interface To connect a suitable peripheral device for analogue processing of the measurements</p>	<p>ZERO Resets the display to "0"</p>	<p>Pallet shipment The time required for internal shipping preparations is shown in days in the pictogram</p>
<p>Length measurement Captures the geometric dimensions of a test object or the movement during a test process</p>	<p>Analogue output For output of an electrical signal depending on the load (e.g. voltage 0 V - 10 V or current 4 mA - 20 mA)</p>	<p>Rechargeable battery pack Rechargeable set</p>	
<p>Focus function Increases the measuring accuracy of a device within a defined measuring range</p>	<p>Statistics Using the saved values, the device calculates statistical data, such as average value, standard deviation etc.</p>	<p>Plug-in power supply 230V/50Hz in standard version for EU. On request GB, AUS or US version available</p>	
<p>Internal memory To save measurements in the device memory</p>	<p>PC Software To transfer the measurement data from the device to a PC</p>	<p>Integrated power supply unit Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or US on request</p>	
<p>Data interface RS-232 Bidirectional, for connection of printer and PC</p>	<p>Printer A printer can be connected to the device to print out the measurement data</p>	<p>Motorised drive The mechanical movement is carried out by an electric motor</p>	
<p>Profibus For transmitting data, e.g. between scales, measuring cells, controllers and peripheral devices over long distances. Suitable for safe, fast, fault-tolerant data transmission. Less susceptible to magnetic interference</p>	<p>Network interface For connecting the scale/measuring instrument to an Ethernet network</p>	<p>Motorised drive The mechanical movement is carried out by a synchronous motor (stepper)</p>	
<p>Profinet Enables efficient data exchange between decentralised peripheral devices (balances, measuring cells, measuring instruments etc.) and a control unit (controller). Especially advantageous when exchanging complex measured values, device, diagnostic and process information. Savings potential through shorter commissioning times and device integration possible</p>	<p>KERN Communication Protocol (KCP) It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems</p>	<p>Fast-Move The total length of travel can be covered by a single lever movement</p>	
<p>Data interface USB To connect the measuring instrument to a printer, PC or other peripheral devices</p>	<p>GLP/ISO record keeping of measurement data with date, time and serial number. Only with SAUTER printers</p>		

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.